## E - 105CITY OF LAS VEGAS & CITY OF HENDERSON STANDARDS 03-23-2023 PG. 1 OF 1 TEMP. CONST. POWER THROUGH MAIN ELECT. - BLDG. SRVC SINGLE FAM. DWELLINGS Henderson Las Vegas Building & Safety Dept. Building & Fire Safety Dept. 240 Water Street Henderson, NV 89015 495 S. Main Street Las Vegas, NV 89106 (702) 267-3650 (702) 229-6251 2018/2021 IBC - 2017 NEC FRAMING SUPPORTS MUST BE 2-1/2" ANGLE IRON, OR 1-5/8" X 3-5/8" 16 GA. STEEL STUDS EMBEDDED IN CONCRETE. THE SERVICE PANEL IS TO BE SECURED PER MANUFACTURERS INSTRUCTIONS. 5990 ALL RECEPTACLES FOR CONSTRUCTION POWER SHALL BE GFCI PROTECTED PER NEC 590.6 AND MUST BE RIGIDLY ATTACHED TO THE STRUCTURE OR SERVICE EQUIPMENT. THE GROUNDING ELECTRODE IS TO BE MOUNTED IN THE SAME BAY AS THE SERVICE. THE GROUNDING ELECTRODE CONDUCTOR IS TO BE SIZED PER NEC, TABLE 250.66 AND IS TO BE INSTALLED PER NEC 250.64. THE ADDRESS IS TO BE POSTED ON THE SERVICE FOR THE INSPECTION. LOCATE THE METER 4 FT MIN. AND 6 FT 3" MAX. ABOVE FINISHED GRADE. TEMPORARY WEATHERPROOFING SHALL BE PROVIDED TO (1) (1) PROTECT ELECTRICAL EQUIPMENT FROM RAIN OR WINDBORNE CONCRETE ENCASED ELECTRODE REQUIRED. GROUND CLAMP LISTED FOR REBAR. ΔΔ 40